

Drop In Anchor



Features and Benefits

- European approval for structural applications in non-cracked concrete
- European approval for non-structural applications in cracked and non-cracked concrete
- Installation prior to the material to be fixed

Applications


- Fixing suspended ceilings, sprinklers and ventilation systems
- Structural fixing, inner and outer ironworks
- Fixing threaded bars

BSUA Zinc Plated



Article Code	Size	Drill Ø mm	Drill Depth mm	Box	Carton
BSUA0625	M6x25	8	25	100	4,000
BSUA0825	M8x25	10	25	100	1600
BSUA0830	M8x30	10	30	100	2,200
BSUA1025	M10x25	12	25	50	800
BSUA1040	M10x40	12	40	50	1,000
BSUA1225	M12x25	15	25	50	800
BSUA1250	M12x50	15	50	50	600
BSUA1665	M16x65	20	65	25	250
BSUA2080	M20x80	25	80	25	100
BSU2080	M20x80	25	80	25	100

BSUAR Stainless Steel A4



Article Code	Size	Drill Ø mm	Drill Depth mm	Box	Carton
BSUAR0625	M6x25	8	25	100	4,000
BSUAR0830	M8x30	10	30	100	2,200
BSUAR1040	M10x40	12	40	50	1,000
BSUAR1250	M12x50	15	50	50	600
BSUAR1665	M16x65	20	65	25	250
BSUAR2080	M20x80	25	80	25	100
BSUAR2080	M20x80	25	80	25	100



Normal Concrete



Reinforced Concrete



Hollow Core Slab